

Разъемы с высокой степенью защиты

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: doc@nt-rt.ru || сайт: <https://degson.nt-rt.ru>



50A-70A

Small size, UL and TUV certification, safe and fast connection



ESP-50A-06-OR-00

Energy storage connector, product range :ESP plug, color: orange, wire section :6mm², rated voltage :1000V, rated current :50A, connection mode: crimped, contact mode: open hole, minimum diameter 4.9mm, maximum diameter 6mm



ESP-70A-10-OR-00

Energy storage connector, product range :ESP plug, color: orange, wire section :10mm², rated voltage :1000V, rated current :70A, connection mode: crimped, contact mode: open hole, minimum diameter 4.9mm, maximum diameter 6mm



ESS-50A-06-B-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 6 mm², rated voltage: 1000V, rated current: 50 A, connection method: copper bar, contact type: pin



ESS-50A-06-S-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 6 mm², rated voltage: 1000V, rated current: 50 A, connection method: screw, contact type: pin



ESS-50A-06-C-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 6 mm², rated voltage: 1000V, rated current: 50 A, connection method: crimping, contact type: pin



ESS-50A-06-B/S-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 6 mm², rated voltage: 1000V, rated current: 50 A, connection method: copper bar/threaded hole, contact type: pin



ESS-70A-10-B-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 10 mm², rated voltage: 1000V, rated current: 70 A, connection method: copper bar, contact type: pin



ESS-70A-10-S-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 10 mm², rated voltage: 1000V, rated current: 70 A, connection method: screw, contact type: pin



ESS-70A-10-C-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 10 mm², rated voltage: 1000V, rated current: 70 A, connection method: crimping, contact type: pin



ESS-70A-10-B/S-OR-00

Energy storage connector, product range: ESS socket, color: orange, wire cross section: 10 mm², rated voltage: 1000V, rated current: 70 A, connection method: copper bar/threaded hole, contact



100A-120A

180°connection and 90°connection, short and long, easier connection



ESP-100A-16-OR-00

Energy storage Connector, Product range: ESP plug, color: orange, Wire cross section: 16 mm², Rated voltage: 1500V, Rated current: 100 A, Connection method: crimp, Contact type: hole type, min. Cable diameter: 7.5 mm, Max. Cable diameter: 9 mm



ESP-120A-25-OR-00

Energy storage connector, Product range: ESP plug, color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: crimped, Contact type: hole type, min. Cable diameter: 9 mm, Max. Cable diameter: 10.5 mm



ESS-100A-16-B-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 16 mm², Rated voltage: 1500V, Rated current: 100 A, Connection method: Busbar, Contact type: Pin



ESS-100A-16-S-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Lead cross section: 16 mm², Rated Voltage: 1500V, Rated current: 100 A, Connection method: Screw, Contact type: Pin



ESS-100A-16-C-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 16 mm², Rated voltage: 1500V, Rated current: 100 A, Connection method: Crimp, Contact type: Pin



ESS-100A-16-B/S-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 16 mm², Rated voltage: 1500V, Rated current: 100 A, Connection method: Busbar/Screw, Contact type: Pin



ESS-120A-25-B-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: Busbar, Contact type: Pin



ESS-120A-25-S-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: Screw, Contact type: Pin



ESS-120A-25-C-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: Crimp, Contact type: Pin



ESS-120A-25-B/S-OR-00

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: Busbar/Screw, Contact



150A-200A

IP67 high protection level, UL and TUV certification, positive and negative mechanical anti-fool design



ESP-150A-35-OR-90

Energy storage Connector, Product range: ESP plug, color: orange, Wire cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: crimped, Contact type: hole type, min. Cable diameter: 11mm, Max. Cable diameter: 12.5 mm



ESP-200A-50-OR-90

Energy storage Connector, Product range: ESP plug, color: orange, Wire cross section: 50 mm², Rated voltage: 1500V, Rated current: 200 A, Connection method: crimp, Contact type: hole type, min. Cable diameter: 12.5mm, Max. Cable diameter: 14mm



ESS-150A-35-B-OR-90

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: Busbar, Contact type: Pin



ESS-150A-35-S-OR-90

Energy Storage Connector, Product range: ESS socket, Color: orange, Lead cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: Screw, Contact type: Pin



ESS-150A-35-B/S-OR-90

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: Busbar/Screw, Contact type: Pin



ESS-200A-50-B-OR-90

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 50 mm², Rated voltage: 1500V, Rated current: 200 A, Connection method: Busbar, Contact type: Pin



ESS-200A-50-S-OR-90

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 50 mm², Rated Voltage: 1500V, Rated current: 200 A, Connection method: Screw, Contact type: Pin



ESS-200A-50-C-OR-90

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 50 mm², Rated voltage: 1500V, Rated current: 200 A, Connection method: Crimp, Contact type: Pin



250A-300A

UL and TUV certification, IP67 high protection level, positive and negative mechanical anti-fool design

Socket panel size covers a wide range



250A Single-core High-current Plug

Energy storage connector, product range: plug, color: orange, wire cross-sectional area: 70mm², rated voltage: 1500V, rated current: 250A, wire cross-sectional area: 70mm², minimum cable diameter: 15.5mm, maximum cable diameter: 17mm, protection class: IP67.



250A Single-core High-current Socket

Energy storage connector, product range: socket, color: orange, rated voltage: 1500V, rated current: 250A, protection level: IP67.



ESP-250A-70-BK-00

Energy storage connector, product range: ESP plug, color: black, wire cross section: 70 mm², rated voltage: 1500V, rated current: 250 A, connection method: crimping, contact type: hole type, minimum cable diameter: 15.5mm, maximum cable diameter: 17 mm



ESP-300A-95-BK-00

Energy storage connector, product range: ESP plug, color: black, wire cross section: 95 mm², rated voltage: 1500V, rated current: 300 A, connection method: crimping, contact type: hole type, minimum cable diameter: 16 mm, maximum cable diameter: 18 mm (non-rotating)



ESP-300A-95-BK-00-01

Energy storage connector, product range: ESP plug, color: black, wire cross section: 95 mm², rated voltage: 1500V, rated current: 300 A, connection method: crimping, contact type: hole type, minimum cable diameter: 16 mm, maximum cable diameter: 18 mm



ESS-200A-50-B/S-OR-90

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 50 mm², Rated voltage: 1500V, Rated current: 200 A, Connection method: Busbar/Screw, Contact type: Pin



ESS-250A-70-B-BK-00

Energy storage connector, product range: ESS socket, color: black, wire cross section: 70 mm², rated voltage: 1500V, rated current: 250A, connection method: copper bar, contact type: hole type



ESS-250A-70-B/S-BK-00

Energy storage connector, product range: ESS socket, color: black, wire cross section: 70 mm², rated voltage: 1500V, rated current: 250 A, connection method: copper bar/threaded hole, contact type: hole type



ESS-250A-70-B-BK-02

Energy storage connector, product range: ESS socket, color: black, wire cross section: 70 mm², rated voltage: 1500V, rated current: 250A, connection method: copper bar, contact type: hole type



ESS-250A-70-B/S-BK-02

Energy storage connector, product range: ESS socket, color: black, wire cross section: 70 mm², rated voltage: 1500V, rated current: 250 A, connection method: copper bar/threaded hole, contact type: hole type



ESS-250A-70-B/S-BK-01

Energy storage connector, product range: ESS socket, color: black, wire cross section: 70 mm², rated voltage: 1500V, rated current: 250 A, connection method: copper bar/threaded hole, contact type: hole type



ESS-300A-95-B-BK-00

Energy storage connector, Product range: ESS socket, color: black, wire cross section: 95 mm², rated voltage: 1500V, rated current: 300 A, connection method: copper bar, contact type: hole type



ESS-300A-95-B/S-BK-00

Energy storage connector, product range: ESS socket, color: black, wire cross section: 95 mm², rated voltage: 1500V, rated current: 300 A, Connection method: copper bar/threaded hole, contact type: hole type (non-rotating)



ESS-300A-95-B-BK-00-01

Energy storage connector, product range: ESS socket, color: black, wire cross section: 95 mm², rated voltage: 1500V, rated current: 300 A, connection method: copper bar, contact type: hole type



ESS-300A-95-B/S-BK-00-01

Energy storage connector, product range: ESS socket, color: black, wire cross section: 95 mm², rated voltage: 1500V, rated current: 300 A, connection method: copper bar/threaded hole, contact



350A-400A

UL and TUV dual certification, IP67 high protection level, positive and negative



ESP-350A-120-BK-00

Energy storage connector, product range: ESP plug, color: black, wire cross section: 120 mm², rated voltage: 1500V, rated current: 350 A, connection method: crimping, contact type: hole type, minimum cable diameter: 19 mm, maximum cable diameter: 22 mm (300A cable available)



ESP-400A-250-BK-00

Energy storage connector, product range: plug, color: black, wire cross-section: 127 mm², rated voltage: 1500V, rated current: 400 A, connection method: crimping, contact type: hole type, minimum cable diameter: 20 mm, maximum cable diameter: 22 mm



ESS-350A-120-B-BK-00

Energy storage connector, product range: ESS socket, color: black, wire cross section: 120 mm², rated voltage: 1500V, rated current: 350 A, connection method: copper bar, contact type: hole type



ESS-350A-120-B/S-BK-00

Energy storage connector, product range: ESS socket, color: black, wire cross section: 120 mm², rated voltage: 1500V, rated current: 350 A, connection method: copper bar/threaded hole, contact type: hole type



ESS-400A-250-B-BK-00

Energy storage connector, product range: ESS socket, color: black, wire cross section: 250 mm², rated voltage: 1500V, rated current: 400 A, connection method: copper bar, contact type: hole type



ESS-400A-250-B/S-BK-00

Energy storage connector, product range: ESS socket, color: black, wire cross section: 250 mm², rated voltage: 1500V, rated current: 400 A, connection method: copper bar/threaded hole, contact

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: doc@nt-rt.ru || сайт: <https://degson.nt-rt.ru>